


Dynamics: Stripping Biogas Permeate. Process Desing and Start-up Study

DESCRIPTION:

Permeate from biogas production, 18000 kg/h, containing 0.6 wt. % of ammonia, 0.3 wt. % of carbon dioxide, and water is to be separated into 15 wt. % ammonia as byproduct. The wastewater must be purified to 50 ppm of ammonia.


The design task is to find distillation column operating parameters and size. This is traditional design according to steady state solution. Ultimate task is to simulate real system in dynamics to determine whether assumed equipment parameters would allow startup and normal operation of the distillation column.

The steady state design gave these results:




Continuing the steady state calculation in CHEMCAD, it would be possible to get concentration, pressure and temperature profiles of the column, as well as tray or packing hydraulic calculations. With CC-Therm module, heat exchangers for condenser and reboiler could be designed. Size of vessels could be determined. **CHEMCAD can do all calculations and produce all documentation required for traditional steady state process design.**

It is more interesting, however, to design and simulate a real system to avoid future operation problems. Steady state calculations have been performed at preparatory stage, to determine required equipment sizes and initial state of the dynamic simulation. For instance, it is necessary to know heat transfer area of heat exchangers and heat transfer coefficient. Sizes of reboiler and overhead tank, as well as initial loads must be determined.



Time after start: 90 minutes


Stream 8 Dynamic Plot



★ Tot. mass rate

Vapor distillate mass flow rate over time


Stream 12 Total Compositions in Mass Fractions



★ Ammonia


◆ Carbon Dioxide

Composition of bottoms. Bottoms can reach desired purity after 52 minutes from the start of the process




★ Tot. mass rate

Reflux rate over time



Composition profile (weight fractions) in the column at last moment of simulation

Distil. Column 3, Stage 1 Liquid



Composition at the top of the column (liquid phase) over time

The presented model can be easily expanded into full system including heat exchangers, control valves, PID controllers, etc.